

# TECH TIPS

Some products have several compatible power supplies while other products must be used with only a specified power supply. This chart is a handy guide for matching power supplies with products. Call SIMCO Customer Service or your local representative if you need additional assistance in selecting the correct product and power supply for your application.

	120V	230V	Ports	Capacity
<b>Aerostats</b>				
AS-2OAF	F167	F267	2 ports	2 AS-2OAFs
AS-2OAF	N167	N267	4 ports	4 AS-2OAFs
XP-2OF — hazardous area	XP167	XP267	4 ports	See chart on page 18
XP-2OF — non-hazardous area	XPM167	XPM267	4 ports	See chart on page 18
<b>Guns</b>				
Cobra	G165	G265	2 ports	2 guns
ES2A4	D167QG		2 ports	2 guns; maximum 20' cable
	N167	N267	4 ports	3 guns; maximum 30' cable
PR55	S165	S265	2 ports	2 guns
<b>Nozzles</b>				
HS	N167	N267	4 ports	200 nozzles
	F167	F267	2 ports	100 nozzles
HS — shielded cable	D167QG		2 ports	20' shielded cable
		N267	4 ports	30' shielded cable
B	H166	H266	2 ports	100 nozzles
HE	D167Q	D257Q	2 ports	100 nozzles
R55	S165	S265	2 ports	2 nozzles
<b>Static Bars</b>				
ME 100/ME 125, MEC	F167	F267	2 ports	200" EL
	D167RY		4 ports	200" EL
	N167	N267	4 ports	300" EL
MEB/MEJ	F167	F267	2 ports	200" EL
	D167Q	D257Q	2 ports	Use with shielded cable. Call SIMCO
	D167RY		4 ports	200" EL
	N167	N267	4 ports	300" EL
PLS/PSH-N *	F167	F267	2 ports	100" EL
	N167	N267	4 ports	150" EL
SS 50	H164	H254	2 ports	200" EL
	N164	N264	4 ports	300" EL
	H166	H266	2 ports	200" EL
SS 75	H166	H266	2 ports	200" EL
	N165	N265	4 ports	300" EL
MESB 125, MESB HR	H166	H266	2 ports	200" EL
	N165	N265	4 ports	300" EL
SM/RSM	S165	S265	2 ports	Maximum 35' bar and cable
The Blue Bar, R50	M167	M267	4 ports	300" w/2.5, 216" w/5 M cable
	D167Q	D257Q	2 ports	300" w/2.5, 216" w/5 M cable
	F167	F267	2 ports	140" w/2.5, 90" w/5 M cable
	N167	N267	4 ports	300" w/2.5, 216" w/5 M cable
The Blue Bar, R51	M165		4 ports	300" w/2.5, 216" w/5 M cable
	D165Q	D255Q	2 ports	300" w/2.5, 216" w/5 M cable
	S165	S265	2 ports	140" w/2.5, 90" w/5 M cable
	N165	N265	4 ports	300" w/2.5, 216" w/5 M cable
7/16" One Point In Line Ionizer	H166	H266	2 ports	2 One Points
	S165	S265	2 ports	2 One Points
Blue Bar HL/XP-2	XP167	XP267	4 ports	See chart on page 18
	XPM167	XPM267	4 ports	See chart on page 18

\* PSH-N and PLS Bars are double bars. Operating lengths per power unit are half the total length of other single bars with same power unit.